

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

IN THE CLAIMS:

Claims 1-34 are pending in the instant application. Claims 8-21 have been cancelled without prejudice. New claims 35-46 have been presented. Applicant requests reconsideration of the claims in view of the following amendments.

Please amend the claims as follows:

1. (Previously presented) An insert earphone comprising:
 - a housing;
 - a receiver located in the housing and having an output port, the receiver for electrically coupling with an audio signal source;
 - a flexible eartip for acoustic sealing with an ear canal of a user; and
 - a tube nipple providing an acoustic pathway through at least one wall of the housing and having a first end and a second end, the first end being located within the housing and being acoustically coupled to the output port of the receiver and the second end being located externally to the housing and being acoustically coupled to the flexible eartip, the tube nipple and housing being configured and arranged to form an obtuse angle between a longitudinal axis of the tube nipple and a vertical axis of the housing, wherein the housing hangs approximately vertically along the side of a user's head when worn; and

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

wherein the insert earphone is inserted at least partially into the ear canal and is supported entirely by the ear canal when worn by the user.

2. (Original) The insert earphone of claim 1 wherein the angle is approximately 118 degrees.

3. (Original) The insert earphone of claim 1 further comprising a flexible channel located between the output port of the receiver and the first end of the tube nipple.

4. (Original) The insert earphone of claim 1 wherein the flexible eartip comprises a flexible tube portion and a foam eartip portion, and wherein at least a portion of the flexible tube portion extends through the foam eartip portion.

5. (Original) The insert earphone of claim 4 wherein the tube nipple is rigid and wherein the second end of the tube nipple is positioned within the flexible tube portion of the flexible eartip.

6. (Previously presented) The insert earphone of claim 1 further comprising an acoustic damper located in the tube nipple proximate the first end of the tube nipple.

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

7. (Original) The insert earphone of claim 3 wherein the flexible channel has a first end and a second end, and wherein the first end of the flexible channel is coupled to output port of the receiver and the second end of the flexible channel is coupled to the first end of the tube nipple.

8. – 21. (Cancelled)

22. (Previously presented) An insert earphone comprising:

- a housing;

- a receiver located in the housing and having an output port, the receiver for electrically coupling with an audio signal source;

- a flexible eartip for acoustic sealing with an ear canal of a user, the flexible eartip having a foam eartip portion and a flexible tube portion;

- a rigid tube nipple providing an acoustic pathway through at least one wall of the housing and having a first end and a second end, the first end of the rigid tube nipple being located within the housing and being acoustically coupled to the output port of the receiver and the second end of the rigid tube nipple being located externally to the housing and being acoustically coupled to flexible tube portion of the flexible eartip; and

- a flexible channel located between the output port of the receiver and the

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

first end of the rigid tube nipple; and

wherein the insert earphone is inserted at least partially into the ear canal and is supported entirely by the ear canal when worn by the user.

23. (Previously Presented) The insert earphone of claim 22 wherein the flexible channel has a first end and a second end, and wherein the first end of the flexible channel is coupled to the output port of the receiver and the second end of the flexible channel is coupled to the first end of the rigid tube nipple.

24. (Previously presented) An insert earphone comprising:

a housing;

a receiver located in the housing and having an output port, the receiver for electrically coupling with an audio signal source;

a flexible eartip for acoustic sealing with an ear canal of a user; and

a tube nipple providing an acoustic pathway through at least one wall of the housing and having a first end and a second end, the first end being located within the housing and being acoustically coupled to the output port of the receiver and the second end being located externally to the housing and being acoustically coupled to the flexible eartip, the tube nipple and housing being configured and arranged to form an obtuse angle of approximately 118 degrees between a longitudinal axis of the tube

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

nipple and a vertical axis of the housing, wherein the housing hangs approximately vertically along the side of a user's head when worn.

25. (Previously presented) The insert earphone of claim 24 further comprising a flexible channel located between the output port of the receiver and the first end of the tube nipple.

26. (Previously presented) The insert earphone of claim 24 wherein the flexible eartip comprises a flexible tube portion and a foam eartip portion, and wherein at least a portion of the flexible tube portion extends through the foam eartip portion.

27. (Previously presented) The insert earphone of claim 26 wherein the tube nipple is rigid and wherein the second end of the tube nipple is positioned within the flexible tube portion of the flexible eartip.

28. (Previously presented) The insert earphone of claim 24 further comprising an acoustic damper located in the tube nipple proximate the first end of the tube nipple.

29. (Previously presented) The insert earphone of claim 25 wherein the flexible channel has a first end and a second end, and wherein the first end of the flexible

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

channel is coupled to output port of the receiver and the second end of the flexible channel is coupled to the first end of the tube nipple.

30. (Previously presented) An insert earphone comprising:

a housing;

a receiver located in the housing and having an output port, the receiver for electrically coupling with an audio signal source;

a flexible eartip for acoustic sealing with ear canal of a user;

a tube nipple having a first end and a second end, the first end located within the housing and acoustically coupled to the output port of the receiver and the second end located externally to the housing and acoustically coupled to the flexible eartip, the tube nipple and the housing being configured and arranged to form an obtuse angle of approximately 118 degrees between a longitudinal axis of the tube nipple and a vertical axis of the housing, wherein the housing hangs approximately vertically along the side of a user's head when worn; and

an acoustic damper located in the tube nipple proximate the first end of the tube nipple.

31. (Previously presented) The insert earphone of claim 30 wherein the flexible eartip comprises a flexible tube portion and a foam eartip portion, and wherein at least

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

a portion of the flexible tube portion extends through the foam eartip portion.

32. (Previously presented) The insert earphone of claim 31 wherein the tube nipple is rigid and wherein the second end of the tube nipple is positioned within the flexible tube portion of the flexible eartip.

33. (Previously presented) The insert earphone of claim 15 further comprising a flexible channel located between the output port of the receiver and the first end of the tube nipple.

34. (Previously presented) The insert earphone of claim 33 wherein the flexible channel has a first end and a second end, and wherein the first end of the flexible channel is coupled to the output port of the receiver and the second end of the flexible channel is coupled to the first end of the tube nipple.

35. (New) An insert earphone comprising:

a housing;

a receiver located in the housing and having an output port, the receiver for electrically coupling with an audio signal source;

a flexible eartip for acoustic sealing with an ear canal of a user, the

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

flexible eartip having a foam eartip portion and a flexible tube portion; and

a tube nipple providing an acoustic pathway through at least one wall of the housing and having a first end and a second end, the first end of the tube nipple being located within the housing and being acoustically coupled to the output port of the receiver and the second end of the tube nipple being located externally to the housing and being acoustically coupled to the flexible tube portion of the flexible eartip;

wherein the earphone providing a response that is approximately 0 dB relative to a response of the TDH-39 standard at at least one of 6 and 8 khz, and wherein the second end of the tube nipple is positioned within the flexible tube portion of the flexible eartip.

36. (New) The insert earphone of claim 35, the tube nipple and the housing being configured and arranged to form an obtuse angle between a longitudinal axis of the tube nipple and a vertical axis of the housing, wherein the housing hangs approximately vertically along the side of a user's head when worn.

37. (New) The insert earphone of claim 36, wherein the angle is approximately 118 degrees.

38. (New) The insert earphone of claim 35, further comprising a flexible channel

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

located between the output port of the receiver and the first end of the tube nipple.

39. (New) The insert earphone of claim 38, wherein the flexible channel has a first end and a second end, and wherein the first end of the flexible channel is coupled to the output port of the receiver and the second end of the flexible channel is coupled to the first end of the tube nipple.

40. (New) The insert earphone of claim 35, further comprising an acoustic damper located in the tube nipple proximate the first end of the tube nipple.

41. (New) An insert earphone comprising:

- a housing;

- a receiver located in the housing and having an output port, the receiver for electrically coupling with an audio signal source;

- a flexible eartip for acoustic sealing with ear canal of a user;

- a tube nipple having a first end and a second end, the first end located within the housing and acoustically coupled to the output port of the receiver and the second end located externally to the housing and acoustically coupled to the flexible eartip;

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

an acoustic damper located in the tube nipple proximate the first end of the tube nipple,

wherein the insert earphone is inserted at least partially into the ear canal and is supported entirely by the ear canal when worn by the user, and wherein the tube nipple and the housing being configured and arranged to form an obtuse angle between a longitudinal axis of the tube nipple and a vertical axis of the housing.

42. (New) The insert earphone of claim 41, wherein the angle is approximately 118 degrees.

43. (New) The insert earphone of claim 41, wherein the flexible eartip comprises a flexible tube portion and a foam eartip portion, and wherein at least a portion of the flexible tube portion extends through the foam eartip portion.

44. (New) The insert earphone of claim 43, wherein the tube nipple is rigid and wherein the second end of the tube nipple is positioned within the flexible tube portion of the flexible eartip.

45. (New) The insert earphone of claim 41, further comprising a flexible channel located between the output port of the receiver and the first end of the tube nipple.

Appl. No. 09/676,722
Amendment dated: JULY 16, 2004
Reply to Office Action of: July 7, 2004

46. (New) The insert earphone of claim 45, wherein the flexible channel has a first end and a second end, and wherein the first end of the flexible channel is coupled to the output port of the receiver and the second end of the flexible channel is coupled to the first end of the tube nipple.